

Recommendations

Goods test performance conditions

- before being tested transport box is conditioned no less than 24 h at the temperature (21±2)°C and relative degree of humidity (65±5)%.

Usage and filling conditions

- if there is a violation of temperature conditions when transporting (less than 1°C or more than 35°C), products should be conditioned during 24 h at the temperature (21±2)°C before being utilized.
- the maximum temperature of the filled product is 70 °C;
- the maximum temperature of the product at lid closing is 35 °C.

Palletizing conditions

- produce should be placed on level pallets without cracks or other defects, which may potentially damage or fail to sustain products;
- maximal load on container lids in the lower layer at a temperature of 20°C must not exceed weight, specified in the individual datasheet for each product;
- it is recommended to lay a corrugated board on a pallet in case of any gaps between the boards of more than 50 mm to distribute load;
- pallet with finished products must be packed in heat shrinkable or stretch tape from top to bottom for fixation against the impact in the vertical and horizontal planes;
- stretch tape wrap of goods must not be strong in order to avoid overtraining and deformation of the goods on the pallets;
- while the finished products are being stuck up on the pallet without boxes, the layers should be layered with cardboard. Especially it is important in the hot seasons of the year. This cardboard layering will allow to obtain a stiffer and consequently more stable pallet.

Warehouse storage conditions

- store at the temperature of 1 to 35 ° C in sheltered storage facilities at a distance of at least 1 m from heating appliances;
- protect from sunlight;
- mind manipulation signs "Top", "Fragile", "Protect from rain", "Stacking-up is limited to 4" on boxes during storage;
- while packed products are being stored in warehouses during heated term with a temperature above 30°C it is recommended to install pallets in the lower tiers with the possibility of airing.

Transportation conditions

- transport by means of closed modes of transport;
- do not add to the pallets load any extra one;
- it is not allowed to transport polymeric consumer transport box without its formation into transport packaging
- transport packages placement in the vehicle should ensure runaway absence and vertical position deviation by more than 5 ° (no pendulum oscillation) during transportation.

IMPORTANT! Warehousing of a larger number of containers, as well as storage of containers with appropriate packaging (heat-shrinkable tape, corrugated cardboard gaskets, etc.) must be checked by individual tests. These recommendations are dictated by the practice of many consumers using disposable polypropylene packaging.